

C A S E S T U D Y

AMIAD WATER SYSTEM FOR PHOSPHORUS REDUCTION

CLIENT:

Kosciusko Thredbo Pty Ltd (KT) WWTP, Alpine Way Thredbo Village.

BACKGROUND:

Phosphorus occurs in natural water and waste waters. Both domestic and industrial waste flows are the major sources of phosphorus levels in municipal wastewater. About 30 to 50% of the phosphorus in domestic wastewater comes from human wastes and the remaining 50 to 70% comes from synthetic detergents used in the laundering of clothes. The presence of excess phosphorus in effluent discharged to natural water bodies has the potential to cause algal blooms and eutrophication.

Kosciusko Thredbo Pty Ltd (KT) currently operates a sewage treatment plant, which services the Thredbo Alpine Village. The treatment plant employs secondary treatment with nitrogen and phosphorus reduction. The original treatment plant consisted of an intermittent extended aeration plant (IEA) and continuous extended aeration plant (CEA), alum dosing for phosphorus reduction, maturation ponds for effluent polishing and UV disinfection prior to discharge to a wetland area and subsequently into the Thredbo River.

DESIGN PARAMETERS:

The NSW EPA advised Kosciusko Thredbo Pty Ltd to upgrade its treated effluent water quality, particularly with respect to the discharge levels of phosphorus. The current EPA licence allows Kosciusko Thredbo Pty Ltd to discharge effluent with a phosphorus concentration of 0.3 mg/l on a 90th percentile basis. This replaced the former licence that had a 50th percentile limit of 0.3 mg/l and 90th percentile limit of 0.7 mg/l.

C A S E S T U D Y

THE CHALLENGE:

As a result of the above licence changes and in order for the treatment plant to consistently meet the licence limit, Kosciusko Thredbo Pty Ltd contracted Amiad Water Systems to install a tertiary filter system with alum dosing to treat effluent from the existing maturation ponds prior to discharge through the existing UV disinfection plant. A pressure filter system was installed with a capacity to treat an average flow of 12 l/s and a peak flow of 20 l/s.



RECOVERY AND THE RESULT:

The scope of works for this contract generally included Project Management, Manufacture, Supply, Installation, Testing and Commissioning of a treatment system comprising, duty/standby feed pumps inclusive of variable frequency drives, four pressure deep media filter vessels complete with piping, valves, instruments, controls, duty/standby backwash pumps, air scour blower, duty/standby alum dosing pumps, sodium hypochlorite dosing pump and chemical storage.

The system design provides for phosphorus reduction and also provides excellent turbidity reduction, which maximizes the efficiency of the downstream sodium hypochlorite and UV disinfection. Similar Amiad systems are commonly used to reach the EPA's Class A water quality standard for unrestricted reuse applications.

Victoria Melbourne
ph 03 9358 5800
fax 03 9358 5888

NSW Sydney
ph 02 9686 7299
fax 02 9686 7653

Queensland Brisbane
ph 07 3279 4700
fax 07 3279 4030

Western Australia Perth
ph 08 9309 3588
fax 08 9309 2844

SA/NT Adelaide
ph 08 8272 3000
fax 08 8272 3200